

Growatt CP1000TL

Leading - edge Technology

- ▶ High conversion efficiency of 98.6% deliver more energy
- ▶ Powerful grid management functions (including LVRT)
- ▶ Active power continuous adjustment (0-100%)
- ▶ Reactive power continuous adjustment (0-100%)
- ▶ Integrated with SCADA monitoring system, totally compatible with smart-grid interface
- ▶ Intelligent control, entirely meet the requirements of grid
- ▶ Provide a turnkey solution, easy installation and maintenance
- ▶ Comprehensive protection for overvoltage, islanding, short-circuit, overload, etc



EU-SOLAR LTD.

A: Hungary 7635 Pécs, Abaligeti út 14.

T: +36 (20) 800 4000 E: petreandras@growatt.hu

Growatt CP1000TL

Input Data

Max. DC power	1150KW
Max. DC voltage	1000V
DC Voltage Range	450V - 1000V
MPPT Voltage Range	450V - 820V
Rated Input Voltage	600V
Start Voltage/Power	500V/1000W
Maximum Input Current	2540A
Number of Independent MPPT	1
Number of DC Inputs	2x8

Output (AC)

Rated AC Power	1000KVA
Rated AC Voltage	270V
AC Voltage Range	210V - 310V
Rated Frequency	50Hz/60Hz
Frequency Range	45Hz-55Hz/55Hz-65Hz
Maximum Output Current	2400A
Power Factor (cosφ)	0.9lagging – 0.9leading
Total Harmonic Distortion	<3%(@Pac,r)

Efficiency

Maximum Efficiency	98.6%
Euro Efficiency	98.3%
MPPT Efficiency	99.9%

Protection

DC Disconnection Device	DC circuit breaker
AC Disconnection Device	AC circuit breaker
DC Overvoltage Protection	Surge arrester type II
AC Overvoltage Protection	Surge arrester type II
Grid monitoring/Management	yes/yes
Ground monitoring	yes
Over Temperature Protection	yes
Insulation monitoring	yes

General Data

Dimension (W/H/D)	6058/2896/2348 mm
Weight	6000kg
Operating Temperature Range	-25 °C ... +50 °C
Relative Humidity	0 - 95%
Degree of Protection	IP 54
Noise Emission	65dB(A)@1m
Maximum Operating Altitude	6000m(Derating over 3000m)
Standby consumption	<200W
Cooling	Air Forced
Topology	Low Frequency Transformer
Display	Touch screen LCD
Communication Interface	RS 485/ Ethernet

Certificates and Approvals

CE/TUV, CQC, CGC, LVRT